

# Acrylic Fiber Packing

Code: KXTP601



## Description

Acrylic fiber packing braided from high strength acrylic fiber with PTFE impregnated twice time. It has excellent properties of sealing, lubricating and resistant to chemical. The acrylic packing can be with or without oil. High elastic red silicone rubber core can absorb vibration.

## KXTP601R -- Acrylic Fiber Packing with Rubber Core

Rubber core can absorb vibration, to control leakage, suitable for worn-out pumps.



Item no.: KXTP601

## Acrylic Fiber Packing

Item no.: KXTP601

\* Especially for the condition of middle temperature.  
High pressure, high speed,.

\* Has excellent properties of sealing, lubricating and resistance to chemicals

## Typical Application

\* Wide variety of uses throughout a plant.

\* Pumps and valves, and can handle more chemicals except strong acid, strong alkali and strong oxidizer.

## Technical Data

Material	100% Acrylic fiber and PTFE
Temperature Range	-50 up to +260 oC
Rotating	20 bar
Reciprocating	80 bar
Static	100 bar
Shaft Speed	20 m/s in rotary
PH	1~13
Density	1.3g/cm3

Copyright © 2014-2015

Ningbo Kaxite Sealing Materials Co., Ltd.

No.134,Huancheng North Road,Jiangbei District,Ningbo City,Zhejiang Province,China (Zip:315020)

Website:<http://www.seal-china.com> E-mail:[sales@seal-china.com](mailto:sales@seal-china.com),[kaxite@seal-china.com](mailto:kaxite@seal-china.com)